

DOOR SOLUTIONS

**We recommend a professional door refinisher to refinish your fiberglass door.
You can also contact your local paint store.**

BASIC STEPS - See manufacturer's instructions for details and safety precautions.

1. Remove Old Finish

To remove topcoat, use Klean-strip® GAR343 (gallon size, QAR343 for quart size) Aircraft Remover or Rustoleum® Aircraft Remover. Follow the manufacturer's instructions.

2. Staining

Once the door is dry, use a paint brush to apply Minwax® Gel Stain (match closely as possible to the original color) evenly in the same direction as the wood-grain on the door. Lightly remove excess stain with a clean, dry and lint- free cloth. Let stain dry according to manufacturer's instructions. Repeat as necessary to achieve the desired look.

3. Top Coat

After stain is dry, apply a coat of clear exterior-grade urethane topcoat with UV inhibitor. A satin sheen is recommended. The coat can be either sprayed or brushed on. Apply evenly and smoothly in the same direction as the wood-grain. Let the clear coat dry according to manufacturer's directions. Lightly sand between coats with 600-grit sandpaper. Apply at least 2 to 3 coats for best result.

4. Refinish Maintenance

Apply 2 coats of exterior-grade topcoat when signs of deterioration or fading is apparent. Note that deterioration of the topcoat or paint will depend upon the level of exposure to the sun and outside elements.